

OFF ROAD ADDITIVE PACKAGE T5050 FOR HYDRAULIC TRANSMISSION BRAKE

●Introduction

T5050 provides superior wear protection for gear, good performance of hydraulic system, inhibit oxidation in order to ensure the service life of the oil. It is a high quality economic additive for the hydraulic transmission brake oil, it specifically blends oil for combine harvesters and tractors and other farm machinery and construction machinery which have one lubrication system for transmission device, hydraulic, gear, brake.

●Recommended Treat Rate (wt%): 8.4

●Specifications

Item	Typical Value	Test Method
Appearance	Red Brown Transparent Liquid	Visual
Kinematic Viscosity (100°C), mm ² /s	By Report	GB/T 265
Flash Point (COC), °C	> 110	GB/T 3536
Calcium, wt%	0.55	ASTM D5185
Zinc, wt%	1.6	ASTM D5185
Phosphorus, wt%	2.11	ASTM D5185
Nitrogen, wt%	0.69	SH/T 0224

●Package, Handle & Storage

1. Packed in 200L metal drum, IBC-Tank or made to order.
2. Long term storage temperature should not exceed 45°C.
3. Handle & blending temperature should not exceed 65°C.
4. Not dangerous chemical, store in dry & clean warehouse.